

INNOVATIVE ORGANICS

MSDS

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: **AmberClean 203V**

Manufacturer: INNOVATIVE ORGANICS
 SAINT-GOBAIN CERAMIC MATERIALS
 4905 East Hunter Avenue
 Anaheim, CA 92807

Emergency information: Chemtrec, 1-800-424-9300

Product information: 1-714-701-3900

2. COMPOSITION INFORMATION

Component	CAS Number	%	OSHA Hazard	Exposure Limits
PRODUCT COMPOSITION IS PROPRIETARY.				

*As defined by SARA, Title 3 and California Proposition 65.

**Not Established

3. HAZARDS IDENTIFICATION

Emergency Overview

Physical Characteristics: Clear colorless liquid, mild odor.

Warning Statements: Will cause eye irritation. May cause skin irritation on prolonged or repeated exposure.

Potential Health Effects

EYES: Will cause moderate eye irritation. May cause permanent eye damage.

SKIN: Prolonged or repeated exposure may cause irritation and dermatitis.

AmberClean 203V

3. HAZARDS IDENTIFICATION (CONTINUED)

INHALATION: Not a hazard under normal conditions. May cause irritation to respiratory tract on exposure to heated vapors or concentrated mists.

INGESTION: May cause stomach ache, nausea, diarrhea, vomiting and headache.

SIGNS and SYMPTOMS: Skin/eye irritation, stomach ache, nausea, diarrhea, vomiting and headache.

4. FIRST AID MEASURES

EYES: Rinse with large quantities of water for at least 15 minutes. Call a physician immediately.

SKIN: Rinse with large quantities of water for at least 15 minutes.

INHALATION: Remove to fresh air.

INGESTION: Dilute stomach contents with water. Do not induce vomiting.
Call a physician immediately.

5. FIRE FIGHTING MEASURES

FLASH POINT (METHOD): 61 °C (closed cup)

FLAMMABILITY CLASS: NFPA Class IIIA

FLAMMABILITY LIMITS IN AIR, % BY VOLUME, Upper 11.4, Lower 1.5

FIRE AND EXPLOSION HAZARD: Thermal decomposition can release irritating vapors.

EXTINGUISHING MEDIA: Foam, CO₂, dry powder or water spray.

FIRE FIGHTING INSTRUCTIONS: Use normal procedures for fighting chemical fires. Cool containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO TAKE IF MATERIAL IS SPILLED OR RELEASED:

Eliminate all ignition sources. Stop spill at source. Contain and absorb with vermiculite or other inert material. Collect spills in appropriate containers for disposal.

SPILL PRECAUTIONS: Eliminate all ignition sources. Wear appropriate protective equipment.

AmberClean 203V

7. HANDLING AND STORAGE

STORAGE AND TRANSPORTATION CONDITIONS:

Avoid temperatures above 61 °C.

HANDLING: Avoid contact with skin and eyes. Wash thoroughly after handling.

STORAGE: Store in cool area out of direct sun light. Prevent contamination and evaporation by keeping containers tightly closed when not in use.

8. PERSONAL PROTECTION AND EXPOSURE CONTROLS

RESPIRATORY PROTECTION: In areas of insufficient ventilation wear suitable organic vapor respirator.

VENTILATION: Use mechanical ventilation in confined areas.

PROTECTIVE GLOVES: Solvent resistant such as PVA.

EYE PROTECTION: Goggles recommended.

OTHER PROTECTIVE EQUIPMENT: As necessary to avoid eye and skin contact.

EXPOSURE GUIDELINES: None established.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear colorless liquid, mild odor.

BOILING POINT: 150 °C

MELTING POINT: <0 °C

SPECIFIC GRAVITY (H₂O=1): 1.03

% VOLATILES BY VOLUME: 100%

WATER SOLUBILITY (% vol): Soluble

pH (neat, unless specified): n/a

VAPOR DENSITY: 4

VAPOR PRESSURE @ 20 °C: 2.2 mbar

EVAPORATION RATE (BUTYL ACETATE =1): <1

10. STABILITY AND REACTIVITY

STABILITY: Product is stable. **CONDITIONS TO AVOID:** Temperatures > 61 °C, strong acids, bases and oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None.

AmberClean 203V

11. TOXICOLOGICAL INFORMATION

EYES: This product has not been tested.

SKIN: This product has not been tested.

INHALATION: LC50 (8 hr. /rat) >5000 mg/m3 (est.)

INGESTION: LD50 (mouse) >2500 mg/m3 (est.)

CHRONIC TOXICITY: Repeated or prolonged exposure may cause eye and skin irritation.

CARCINOGENICITY: No single component is known to be carcinogenic or mutagenic.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: Expected to be toxic to fish and aquatic life.
Do not allow contact with open waters or wetlands.

ENVIRONMENTAL FATE: Readily biodegradable. Accumulation unlikely.

13. DISPOSAL INFORMATION

WASTE DISPOSAL METHODS:

Waste disposal procedures must be in accordance with government and local regulations.
It is reasonable to expect that uncontaminated product can be disposed of through a sanitary sewer or similar bio-remediation system.

EMPTY CONTAINER DISPOSAL:

Rinse product drums with clean water. Dispose of rinse water as product requiring treatment.

WASTE CLASSIFICATION: If discarded in its purchased form, this product is not a RCRA hazardous waste.

14. TRANSPORTATION INFORMATION

DOT & IATA INFORMATION

SHIPPING NAME: Ethyl lactate

HAZARD CLASS: 3

UN/NA NUMBER: UN 1192

PACKAGING GROUP: III

LABELS REQUIRED: Flammable liquid

AmberClean 203V

15. REGULATORY INFORMATION

UNITED STATES FEDERAL REGULATIONS:

CERCLA SECTION 103: This product contains the following chemicals that require notification of the National Response Center of release of quantities greater than the reportable quantity:

None.

SARA SECTION 302: This product contains the following chemicals requiring emergency planning:

None.

SARA SECTION 311/312 HAZARD CATEGORIES:

Immediate health hazard.

SARA SECTION 313: This product contains the following chemicals subject to the reporting requirements of the Emergency Planning and Community Right to Know Act:

None.

STATE RIGHT-TO-KNOW REGULATIONS:

California Proposition 65: This product does not contain any chemicals known to the state of California to cause cancer or birth defect:

INTERNATIONAL REGULATIONS:

None known.

CHEMICAL INVENTORIES: This product's ingredients are on the following chemical inventories:

TSCA

16. OTHER INFORMATION

HAZARDOUS MATERIALS INFORMATION SYSTEM (HMIS)

HEALTH	1	SUMMARY OF RATINGS SCALE 0 No significant risk to health 1 Slight hazard 2 Moderate hazard 3 Serious hazard 4 Severe hazard
FLAMMABILITY	2	
REACTIVITY	0	
PERSONAL PROTECTION	C	

WHILE SAINT-GOBAIN BELIEVES THAT THE DATA AND INFORMATION CONTAINED HEREIN ARE FACTUAL AND THE OPINIONS ARE THOSE OF QUALIFIED EXPERTS, THEY ARE NOT TO BE TAKEN AS A WARRANTY OR REPRESENTATION FOR WHICH SAINT-GOBAIN ASSUMES ANY LEGAL RESPONSIBILITY. THEY ARE OFFERED SOLELY FOR THE CONSIDERATION, INVESTIGATION AND VERIFICATION BY THE USER. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS PRODUCT, DATA AND INFORMATION IN ACCORDANCE WITH APPLICABLE LAWS AND REGULATIONS

ACL203V.404

Last revision: 4/23/04-DW

AmberClean 203V

DEFINITIONS

SUMMARY OF HMIS RATINGS

HEALTH HAZARD RATINGS

- O No significant risk to health.
- 1 Irritation or minor reversible injury possible.
- 2 Temporary or minor injury may occur.
- 3 Major injury likely unless prompt action is taken and medical treatment is given.
- 4 Life-threatening, major or permanent damage may result from single or repeated exposures.

FLAMMABILITY HAZARD RATINGS

- O Materials that are normally stable and will not burn unless heated.
- 1 Materials that must be preheated before ignition will occur. Flammable liquids in this category will have flash points at or above 200°F (NFPA Class IIIB).
- 2 Materials that must be moderately heated before ignition will occur, including flammable liquids with flash points at or above 100°F and below 200°F (NFPA Class II & IIIA).
- 3 Materials capable of ignition under almost all normal temperature conditions, including flammable liquids with flash points below 73°F and boiling points above 100°F as well as liquids with flash between 73°F and 100°F (NFPA Class IB & IC).
- 4 Very flammable gasses or very volatile, flammable liquids with flash points below 73°F and boiling points below 100°F (NFPA Class IA).

REACTIVITY HAZARD RATING

- O Materials that are normally stable, even under fire conditions and will not react with water.
- 1 Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but they will not release energy violently.
- 2 Materials that are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water.
- 3 Materials that are capable of detonation or explosive reaction, but require a strong initiating source or must be heated under confinement before initiation, or materials that react explosively with water.
- 4 Material that are readily capable of detonation or explosive decomposition at normal temperatures and pressures.

PERSONAL PROTECTION INDEX DEFINITIONS

- A Safety glasses
- B Safety glasses, gloves
- C Safety glasses, gloves synthetic apron
- D Face shield, gloves, synthetic apron.
- E Safety glasses, gloves, dust respirator.
- F Safety glasses, gloves, synthetic apron, dust respirator.
- G Safety glasses, gloves, vapor respirator.
- H Splash goggles, gloves synthetic apron, vapor respirator.
- I Safety glasses, gloves, combination dust & vapor respirator.
- J Splash goggles, gloves, synthetic apron, combination dust & vapor respirator.
- K Airline hood or mask, gloves, full protective suit, boots.
- X Ask your supervisor for specialized handling directions.